




PP工程塑料紧固件 聚丙烯 (Polypropylene)

- 该材料为结晶性工程塑料。是工程塑料中比重最小, 且具有耐腐蚀性较好, 是用途最广泛的工程塑料。
- 连续使用温度90℃ ● 燃烧性UL94 HB

图片	名称 (编号)	规格									
		M1.7	M2	M2.6	M3	M4	M5	M6	M8	M10	M12
	六角螺丝 (PP/BT)	M1.7	M2	M2.6	M3	M4	M5	M6	M8	M10	M12
	节距	0.35	0.4	0.45	0.5	0.7	0.8	1	1.25	1.5	1.75
	长度										
	10					○	○	○			
	12					○	○		○		
	15					○	○	○	○	○	
	20					○	○	○	○	○	○
	25					○	○	○	○	○	○
	30						○	○	○	○	○
	35									○	
	40									○	○
	50									○	
70										○	
	六角螺母 (PP/NT)					M4	M5	M6	M8	M10	M12
	节距					0.7	0.8	1	1.25	1.5	1.75
	垫片 (PP/W)					4	5	6	8	10	12
	d x D					4.3x9	5.3x10	6.4x12.5	8.4x17	10.5x21	13x24
	厚度t					0.8	1	1.6	1.6	2	2.5